

FallSafe™

HR20L (FR Webbing)



Class L full body harness suitable for work positioning, fall arrest & work restraint situations with one dorsal attachment D-ring, and two chest attachment D-rings. comfort pad at the shoulder waist & thigh enhances the efficiency of workers during long working hours.

44mm webbing red zig zag 75 GSM FR

CE 0598, 2233

EN 361:2002

Product Specification

Material	Polyester/Nylon
Webbing Width	Min 43 mm
Webbing Thickness	Min 1.8 MM
Breaking Strength	Min 25 KN
Flammability	80 mm / min Max
Attachment Elements	2 chest attachment D-Ring for tower climbing 1 dorsal attachment D-Ring for fall arrest
Chest-Strap	Adjustable
Shoulder Strap	Adjustable
Thigh-Straps	Adjustable
User Capacity	59 - 100 Kgs
Weight	~1400 +/- 100 Gms

SKU Information

Product SKU	Size	Inner pack UPC	Carton GTIN
BLSH-FPH-WOL-HR20-FR	OSFM	810148539993	00811437022387

Applications

- Climbing ladder
- Windmill maintenance

Packaging Information

1 Piece / Polybag
20 Pieces / Carton
Carton Dimension - 65x39x30 cm
Carton Weight - 27 kg / 59.52 lbs