

FallSafe[™]

PA01



 ϵ

EN 795: 2012 Type B

ANSI Z 359.1

Parapet anchors are specially designed so that they do not require fixing elements to the structure and they will Come with one or more fixed anchor points. This device usually requires minimal installation or can be dismantled making the device easily portable. Parapet anchor provides a secure anchor point on parapets and facades for use on various of structures. The rubber pads on the inner side of the adjustable arms also ensure that the parapet does not get damaged.

Features

- O Light weight anchorage point to ensure safe working in suspension position.
- O Designed for parapet to ensure safe working in suspended position.
- Rubber padding supports the working surface and reduces the possibility of damage.
- Two tightening stud handles for even force distribution on the parapet wall.
- O High strength steel construction with built-in D-ring.

Product Specification

Anchor Installation	Reusable	
Anchor Style	Single Point Anchor	
Adjustment Style	Detent Pin	
Clamp Style & Mounting Type	Sliding & Clamp- On	
Mounting Orientation	Horizontal, Vertical	
Material of Construction	Powder Coated MS	
Parapet Protection type	Rubber pads	
Min. & Max. Of Parapet width	60 mm to 370 mm (235 Inch to 14.5inch)	
Overall Dimension	650 mm x 350 mm x 64 mm	
Weight	7.6 Kg	
Confirms to	EN 795:2012 Type B & ANSI Z 359.1	
Tensile Strength & Weight capacity	22 KN & 100 kg	
No. Of user	1 Person	

SKU Information

Product SKU	Inner pack UPC	Carton GTIN
BLSH-FP-PA01	XXXXXXX	XXXXXXXX

Application

- Construction Sites
- Work at Height

