



EN 795:2012 Type A
CEN/TS 16415:2013
Ansi Z359.1



The single point anchor provides permanently fixed and removable anchor devices, allowing a worker to confidently and safely attach connecting devices. Single point anchors can be used in a wide variety of environments and applications, such as construction, general industry, power generation or transmission, wind power, etc.

Features

- Compact and highly corrosion resistant.
- Can be bolted on any structure with the help of only one screw- bolts.
- Tested to withstand the impact load in all the 3 axes, providing the highest level of safety.
- Can be used to anchor to steel, concrete, or rope access systems, meaning it can be used for fall arrest, restraint and work positioning.
- Can be used as Type A anchor in combination with either the Multi-Hole Base plates or Rivet Baseplate.

Product Specification

Material of Construction	EN8D High-strength steel
Finish & Color	Zinc Plated, Golden Chromium
Overall Dimension	L 98 x B 34 x H 78 mm
Wight	0.45 Kgs ± 0.05
Mounting Bolt Size	12mm Bolt
Minimum Breaking Strength	23 KN
Operating Temperature	-30° C to +50° C
Confirms to	EN 795:2012 Type A, CEN/TS 16415:2013, Ansi Z359.1

Applications

- Roof top maintenance
- Gutter cleaning and servicing
- Solar panel installations and maintenance
- Roof light cleaning
- HVAC system servicing

SKU Information

Product SKU	Inner pack UPC	Carton GTIN
BLSH-FP-SPA01	XXXXXXXX	XXXXXXXX