

FallSafe™

UP01



EN 795:2012 Type B
CEN/TS 16415 (Multi User)

Universal post is meant to provide a temporary anchor for working on top of 20 ft & 40 ft shipping containers. In addition to be used as a stand alone anchor post, it can also be used to form a horizontal lifeline over the top of container depending upon the requirement of work to be done.

Key Features

- Provides an elevated anchorage point, which reduces fall clearance.
- Comes with a Screw Handle & lock pad arrangement for secure installation by one person only.
- Can be removed without damaging the container.
- Has an anchorage Point on 4 directions allowing a 360° anchorage point, suitable for most of the connectors.

Product Specification

Anchor Installation	Reusable
Anchor Style	Post Type
Adjustment Style	Stud
Mounting Orientation	Vertical
Material of Construction	CED Coated MS
Attachment Point	4x anchorage holes
Overall Dimension	200 mm x 200 mm x 610 mm
Weight	7.6 Kg
Certified To	EN 795:2012 Type B & CEN/TS 16415 (Multi User)
Static Strength & Min. Breaking Strength	12 KN & 15 KN
No. Of user	1 Person

SKU Information

Product SKU	Inner pack UPC	Carton GTIN
BLSH-FP-UP01	XXXXXXXX	XXXXXXXX