

When it comes to entry/rescue in confined spaces, it is essential that winches operate efficiently and quickly. It provides a means to safely retrieve a disabled worker. We introduce a bi-directional manually operated winch, Equipped with a quick attach mounting clamp which easily mount on our Tripod as well as Modular Davit Arm. The range of winch is available from 10 meters to 30 meters.

CE EN 1496:2017 Class B



Key Features

- Compact design with inbuilt cover to enclosed internal mechanisms.
- Quick attach mounting clamp makes easy and quick installation.
- Locking mechanism equipped with dual safety pawl.
- Bi-directional manually Operated handle.
- Swivel snap hook with load indicator.

Product Specification

Gear Drive & Ratio	6 : 1 spur gear drive
Wire rope	4.8mm Galvanized Wire Rope
Available Length	Available from 10 meters to 30 meters
Material & Finish	Powder coated MS & Zinc Plated Fasteners
Load Capacity	150 Kg
Min. Breaking Strength	12 KN

Applications

- Tanks
- Vessels
- Drainage system
- Sewerage system
- Pharma industry
- Chemical plants

SKU Information

Model number	Product description	Product SKU
W10	Winch 10mtrs	BLSH-FP-W10
W15	Winch 15mtrs	BLSH-FP-W15
W20	Winch 20mtrs	BLSH-FP-W20
W25	Winch 25mtrs	BLSH-FP-W25
W30	Winch 30mtrs	BLSH-FP-W30

