

FLAMMABLE STORAGE CABINETS

EN14470-1 flammable cabinet as a robust industrial talent for the safe and compliant storage of flammable hazardous substances. Many different models and equipment variants are available to you for the various areas of application with 90-minute or 30-minute fire resistance. Extreme fire resistance for high-risk environments such as high occupancy sites, high-value/high asset settings, or remote areas that lack fire-fighting services.



1. Extremely robust design with scratch-proof surface, triple hinged door for extreme strain.
2. Doors stay in place at any opening angle for a more convenient handling of containers.
3. Intumescent strips expand to seal gaps in case of fire.
4. Hybrid-close door—manual close doors stop in any position, but self-close at 122 F (50 °C) under fire conditions.
5. Two top vents with butterfly valve close automatically at 158 F (70 °C) in a fire.
6. Integrated air ducts ready for connection (DN 75) to a technical exhaust system can be used for the extraction of hazardous substances vapours, close automatically at 158 F (70 °C) in a fire.
7. Removable sump with perforated insert captures spills—keeps containers elevated to stay dry.
8. Integrated transport base for simple inhouse transport, cabinet can be transported upright through doors.

Product Specification

Color	Yellow & Light Grey
Bottom Sump Capacity	18 L
Number of Doors	1
Door Type	Wing door
Number of Shelves	3
Dimensions, Exterior	60x61.5x195cm
Dimensions, Interior	49x46x160cm
Capacity of the Largest Single Container	16 L
Net Weight	360 kgs
Extraction air	75 DN
Complies with EN14470-1	Yes
Fire Resistance	90 minutes

Industries



Chemical



Oil & Gas



Pharmaceutical



Aviation



Power



Manufacturing



Automotive



Warehousing