

LITHIUM-ION BATTERY CHARGING CABINETS



The 90 minutes fire resistant lithium-ion battery charging cabinet is suitable for the storage and charging of various types of power tool batteries. The cabinet complies with the EN14470-1 standard. Many different models and equipment variants are available to you for the various areas of application. Extreme fire resistance for high-risk environments such as high occupancy sites, high-value/high asset settings, or remote areas that lack fire-fighting services.

1. A highly sensitive smoke detector is installed on the top of the cabinet. When the smoke detector detects smoke, the buzzer on the front of the cabinet will sound an alarm, will automatically cut off the power to prevent the fire from spreading outward.
2. The cabinet is equipped with steel shelves as standard, and each shelf has multiple heat dissipation ventilation holes to increase the air flow inside the cabinet.
3. The cable connection port has a fireproof function, and the cable connection inside and outside the cabinet is sealed with fireproof putty.
4. The PDU socket has an automatic power-off function. When the smoke detector alarms, the socket can automatically disconnect the power supply to avoid accidents.
5. The cabinet has leakage protection and overload protection functions.
6. Working voltage: AC 220V/50Hz (Can customized according the Country standards)
7. Equip a aerosol fire suppression to reduce the fire risk.
8. Integrated air ducts ready for connection (DN 75) to a technical exhaust system can be used for the extraction of hazardous substances vapours, two top vents with butterfly valve close automatically at 158 F (70 °C) in a fire; Intumescent strips expand to seal gaps in case of fire.
9. Standard PUD industrial socket, you can choose different types of sockets such as European and British standard.
10. Standard circuit installation to effectively avoid safety hazards caused by line fire.
11. Integrated transport base for simple inhouse transport, cabinet can be transported upright through doors.

HazVault™

HVLE1016

Product Specification

Color	RAL 5010 Gentian blue
Bottom Sump Capacity	18 L
Number of Doors	1
Door Type	Self-Closing
Number of Shelves	5 pcs / 20 Outlets
Dimensions, Exterior	60x61.5x195cm
Dimensions, Interior	49x49x160cm
Net Weight	458 kgs
Extraction air	75 DN
Operating Voltage	AC 220V/50Hz
Fire Resistance	90 minutes
Complies with EN14470-1	Yes

Industries



Chemical



Oil & Gas



Pharmaceutical



Manufacturing



Aviation



Power



Automotive



Warehousing