



UltiFlash[®]

EG3102

Heavy duty seamless unlined latex electrical insulating gloves available in the different class range.

STORAGE

Store in original packaging (Opaque packaging used for protection & instructions for use). Do not compact or fold. Do not expose to heat sources (sunlight, radiators, artificial light). Store between 10°C & 21°C.



Category - RC

R = Acid, Oil, Ozone

C = Very Low Temperature

Product Specification

Material	Latex
Class	1
Test Voltage	10000 V
Working Voltage	7500 V
Category	RC
Cuff Style	Straight
Size	9 / 10

Applications

- Power & Utilities
- Electric Public Transport Maintenance
- EV Battery Manufacturing and assembly
- EV Aftermarket Service and Maintenance
- Electrical Maintenance
- Cable Jointing
- Field Services

Industries



Power



Mines



Oil & Gas



Automotive



Construction



Heavy Engineering

Packaging Information

1 Pairs / Printed Polybag
10 Pairs / Carton
Carton Dimension - 79.5x39.5x31.5cm
Carton Weight - TBD

SKU Information

Product SKU	Size	Inner pack UPC	Carton GTIN
BLSH-HDS-EHG9-1	9	810090087115	00810090087122
BLSH-HDS-EHG10-1	10	810090087139	00810090087146

Inspection

Before each use, carry out a visual inspection. Any puncture or perforation makes the gloves unusable.

Precautions

Do not expose to solvents or chemicals that may cause deterioration. Do not use the glove when damp.

Cleaning

Use water & soap. Dry below 65°C with ambient humidity