




Auto Darkening Welding Shield with ADF800SG

Product Specification

Optical Class	1 / 1 / 1 / 1
Viewing Area	97 x 62 mm (3.82" x 2.44")
Cartridge Size	133 x 114 x 9 mm (5.25" x 4.50" x 0.35")
Arc Sensor	4
Light State	DIN 3.5
Dark State	Variable Shade 5 ~ 8 / 9 ~ 13
Shade Control	Internal, Variable Shade
Power On/Off	Automatic On / Off
Sensitivity Control	Low ~ High, by infinitely dial knob
UV/IR Protection	Up to Shade DIN16 at all times
Power Supply	Solar cell. Battery replaceable, 2 x CR2450 lithium battery
Switching Time	1/25,000 s. from Light to Dark
Dark to Light	0.1 ~ 1.0 s by infinitely dial knob
Low Amperage TIG Rated	≥ 2 amps (DC); ≥ 2 amps (AC)
Grinding	Yes
Battery Capacity Test	Yes
Operating Temp.	-10 °C ~ +55 °C (14 °F ~ 131 °F)
Storing Temp.	-20 °C ~ +70 °C (-4 °F ~ 158 °F)
Helmet Material	High Impact Resistance Nylon
Total Weight	490 g
Approved	CE, ANSI, CSA, AS/NZS, EAC



Packaging Information

1 Piece / Box

Box Dimension - 30x26x25 cm

Box Weight - TBD

SKU Information

Product SKU	Inner pack UPC
BLSH-ADWH-W300	810148535339