



# WeldVison™


## W400 Air



Auto Darkening Welding Shield with side lens with ADF900G - Air Version

### Product Specification

|                        |                                                                  |
|------------------------|------------------------------------------------------------------|
| Optical Class          | 1 / 1 / 1 / 1                                                    |
| Viewing Area           | 107 x 75 mm (4.21" x 2.95")                                      |
| Cartridge Size         | 156 x 123 x 33 mm (6.14" x 4.84" x 1.30")                        |
| Arc Sensor             | 4                                                                |
| Light State            | DIN 4                                                            |
| Grind State            | DIN 4                                                            |
| Cutting Shade          | Shade No. from 5 to 8                                            |
| Welding Shade          | Shade No. from 9 to 13                                           |
| Shade Control          | Internal, Digital Display Control                                |
| Power On / Off         | Automatic On / Off                                               |
| Sensitivity Control    | Low ~ High, Digital Display Control                              |
| UV / IR Protection     | Up to Shade DIN13 at all times                                   |
| Power Supply           | Solar cell. Battery replaceable, 2 × CR2450 lithium battery      |
| Switching Time         | 1/25,000 s. from Light to Dark at 55 °C (131 °F)                 |
| Grinding               | Yes                                                              |
| Delay (Dark to Light)  | 0.1 ~ 1.0 s, Digital Display Control                             |
| Low Amperage TIG Rated | ≥ 2 amps (DC); ≥ 2 amps (AC)                                     |
| Operating Temp.        | -5 °C ~ +55 °C (23 °F ~ 131 °F)                                  |
| Storing Temp.          | -20 °C ~ +70 °C (-4 °F ~ 158 °F)                                 |
| Helmet Material        | High Impact Resistance Nylon                                     |
| Total Weight           | 778 g                                                            |
| Approved               | CE, EN175, EN 379, EN166, ANSI Z87. I, CS A Z94.3, AS/NZS 1338.1 |



### Packaging Information

1 Piece / Box

Box Dimension - 33x28.5x25.5 cm

Box Weight - TBD

### SKU Information

| Product SKU        | Inner pack UPC |
|--------------------|----------------|
| BLSH-ADWH-ASL-W400 | 810148535353   |