




Auto Darkening Welding Shield with side lens with ADF900S

Product Specification

Optical Class	1 /1/1/1
Viewing Area	107 x 75 mm (4.21" x 2.95")
Cartridge Size	156 x 123 x 33 mm (6.14" x 4.84" x 1.30")
Arc Sensor	4
Light State	DIN 4
Grind State	DIN 4
Cutting Shade	Shade No. from 5 to 8
Welding Shade	Shade No. from 9 to 15
Shade Control	Internal, Digital Display Control
Power On / Off	Automatic On / Off
Sensitivity Control	Low ~ High, Digital Display Control
UV / IR Protection	Up to Shade DIN 13 at all times
Power Supply	Solar cell. Battery replaceable, 2 x CR2450 lithium battery
Switching Time	1 /25,000 s. from Light to Dark
Grinding	Yes
Delay (Dark to Light)	0.1 ~ 1.0 s, Digital Display Control
Low Amperage TIG Rated	≥ 2 amps (DC); ≥ 2 amps (AC)
Operating Temp.	-10 °C ~ +55 °C (23 °F ~ 131 °F)
Storing Temp.	-20 °C ~ +70 °C (- 4 °F ~ 158 °F)
Helmet Material	High Impact Resistance Nylon
Approved	CE, UKCA, UKNI, ANSI Z87.1, Z94.3, AS/NZS 1338.1, EAC



Packaging Information

1 Piece / Box

Box Dimension - 35x30.5x26.4 cm

Carton Weight - TBD

SKU Information

Product SKU	Inner pack UPC
BLSH-FADWH-ASL-W500	810148535360